



# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

quality.always

## MJ7590EEC443P

MITASU GEAR OIL GL-4 75W-90 Synthetic Blended – multipurpose synthetic blended gear oil, formulated with synthetic base oils and a balanced additive package, safe for non-ferrous metals and alloys.

### APPLICATION

MITASU GEAR OIL GL-4 75W-90 Synthetic Blended is designed for use in mechanical (manual and robotic) gear boxes, transfer boxes and steering mechanisms as well as main gears of cars, buses, SUVs, trucks, and other vehicles where the manufacturer recommended oil with a viscosity of SAE 75W-90 and API GL-4 standard\*.

### SPECIFICATIONS / APPROVALS

- API GL-4

### APPLICATION BENEFITS

MITASU GEAR OIL GL-4 75W-90 Synthetic Blended provides:

- Wear protection to synchronizers and other parts made of nonferrous metals, like bronze, copper and etc.
- Stable performance at temperatures as low as -40 °C
- Increased transmission life
- Increased oil change interval
- Protection from corrosion

*\* API GL-5 oils should not be used in most cases, where the vehicle manufacturer recommends API GL-4 oils*

The latest technologies of MITASU OIL CORPORATION, Japan ensure that transmission oils manufactured by the company comply with the requirements of many automotive manufacturers: TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, DAIHATSU, HYUNDAI, KIA, FORD, BMW, VW, FIAT, AUDI, RENAULT, and others.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	75W-90
Density at 15°C	ASTM D-4052	0,8769
Flash point, °C	ASTM D-92	200
Pour point, °C	ASTM D-97	-40
Colour	ASTM D-1500	<0,5
Viscosity index	ASTM D-2270	192
Kinematic viscosity at 40°C (cSt)	ASTM D-445	92,05
Kinematic viscosity at 100°C (cSt)	ASTM D-445	16,15

Due to continual product research and development, the information contained herein is subject to change without notification.



20L



200L